

S 45XL SPREADER

ART.105.930.5

SPECIFICATIONS:

LENGTH (in/mm): 36.8/935

WIDTH (in/mm): 8.5/215

DEPTH (in/mm): 8.5/215

36.6/16.6 WEIGHT (lbs/kgs):

SPREADING DISTANCE (in/mm): 24/600

OPERATING PRESSURE (psi/bar): 10,500/720

MAX SPREADING FORCE (lbf/KN): 38,250/170

MAX PULLING FORCE (lbf/KN): 9,700/43

NFPA COMPLIANT: YES

NFPA 1936 LSF (lbf/KN): 8,093/36

NFPA 1936 HSF (lbf/KN): 10,903/48.5

NFPA 1936 LPF (lbf/KN): 6,407/28.5

NFPA 1936 HPF (lbf/KN): 8,992/40

SHIPPING WT (lbs/kgs): 50/22.7

BOX SIZE (ft^3/M^3) : 2.16/.061

BOX DIMENSIONS (in/mm):36 x 11.5 x 9

914 x 292 x 229

Features: Constructed of high strength, aircraft

grade, aluminum alloy forgings with a wear resistant anodized finish. The tips on the S45-XL spreader are forged steel. The S45-XL has a folding "D" handle that can be folded out of the way when working in 1936 **NFPA** confined spaces. The S45-XL spreader has a variable speed, "deadman" control with load holding capability **iso** 9001 and over-pressurization relief.





